



PRODUCT DESCRIPTION

ORDER NUMBER

INFRARED BARRIERS WITH ADJUSTABLE LENSES

PHOTOELECTRIC CELLS IN A SHOCKPROOF CASE IP44

Maximum range 25m


Power supply 12/24Vac-dc

Protection grade IP44

Photoelectric cells that are easy and rapid to install, they are fitted with horizontally adjustable lenses through 180°, permitting greater installation flexibility.

The auto-centering lenses also allow slight vertical corrections to be made.

Automatic synchronism eliminates disturbance between two pairs of photoelectric cells.



Dimensions 43 x 102 x 34

SURFACE-MOUNT PHOTOELECTRIC CELLS, RANGE 25m

VED0180

PHOTOELECTRIC CELLS IN A SHOCKPROOF CASE IP44


Maximum range 25m

Power supply 24Vac-dc

Protection grade IP44

Programmable infrared photoelectric cells. Ideal for complex installations with up to 8 pairs of photocells thanks to the synchronism system. They are fitted with horizontally adjustable lenses through 180°, permitting greater installation flexibility and the auto-centering lenses also allow slight vertical corrections to be made.

The devices can be powered with 24 Vac or Vdc without reference to the polarity.



Dimensions 43 x 102 x 34

SURFACE-MOUNT PHOTOELECTRIC CELLS, RANGE 25m

VED0180PRO